



## NOTES:

- TREE TIES AT TWO LOCATIONS, REFER TO SPECIFICATIONS, (FOUR TOTAL) TYP. PROVIDE 5"-6" OF SLACK IN TIES TO ALLOW FOR TREE MOVEMENT IN THE WIND.
- TWO 2" DIAMETER TREATED LODGEPOLE TREE STAKES (SET PLUMB) DO NOT PENETRATE ROOT BALL.
- 3. SECURE TREE TIE WITH GALVANIZED FENCE STAPLE
- 1" X 4" REDWOOD BRACE NAILED TO STAKES WIT GALVANIZED NAILS. 18" ABOVE FINISHED GRADE.
- ROOT BALL, SET CROWN 2" ABOVE FINISH GRADE.PROVIDE POSITIVE DRAINAGE AWAY FROM ROOT BALL.
- 6. WATER RETENTION BERM.
- 7. BARK MULCH, SEE SPECS.
- 8. FERTILIZER PACKET, REFER TO SPECIFICATION TYPE.
- 9. PLANTING PIT TO BE TWICE THE DIAMETER OF ROOT BALL. FOR BACKFILL MIX, REFER TO SPECIFICATIONS.
- 10. SUBSOIL, SEE SPECS.
- 11. REFER TO SPECIFICATIONS AND PLAN SHEETS FOR MORE INFORMATION



TOWN OF PARADISE PUBLIC WORKS / ENGINEERING

Standard Detail L-1
TREE PLANTING DETAIL

5555 Skyway Paradise, California 95969 Phone: (530) 872-6291 Fax: (530) 877-5059

3/30/2023 Approved Date