



NOTES:

1. PORTABLE DELINEATORS PLACED AT ONE-HALF THE SPACING INDICATED FOR TRAFFIC CONES MAY BE USED INSTEAD OF CONES FOR DAYTIME CLOSURES ONLY.
2. SIGN MUST BE EQUIPPED WITH AT LEAST TWO FLAGS FOR DAYTIME CLOSURES. FLAGS MUST BE ORANGE IN COLOR AND AT LEAST 16 INCHES BY 16 INCHES IN SIZE.
3. A G20-2 "END ROAD WORK" SIGN, SHALL BE PLACED AT THE END OF THE SHOULDER CLOSURE UNLESS THE SHOULDER CLOSURE ENDS WITHIN THE LARGER PROJECT'S LIMITS.
4. EITHER TRAFFIC CONES OR BARRICADES SHALL BE PLACED ON THE TAPER. BARRICADES SHALL BE TYPE I, II, OR III.
5. USE CONE SPACING 30' FOR TAPER SEGMENT AND 60' FOR TANGENT SEGMENT.
6. INSTALL TEMPORARY PEDESTRIAN ACCESS ROUTES PER CALTRANS STANDARD PLANS T30-34 IF NECESSARY.
7. DRIVEWAYS SHALL REMAIN OPEN AT ALL TIMES.

SIGN PANEL SIZE (Min)

- A 60" x 36"
- B 36" x 36"
- C 36" x 18"

LEGEND

- TRAFFIC CONE
- ⊥ TEMPORARY TRAFFIC CONTROL SIGN

DATE	OWNER	MS	REVISION DESCRIPTION	APPD DATE



IMPORTANT NOTICE
 Section 4216/4217 of the Government Code
 requires a Dig Alert identification
 number to be issued before a
 "Permit to Excavate" will be valid.
 For your Dig Alert ID, Number call
CALL TOLL FREE
48 HOURS BEFORE YOU DIG
UNDERGROUND SERVICE ALERT
 1-800-227-2800

ENGINEER STAMP:

TRAFFIC CONTROL PLANS DETAIL No. 1 TYPICAL TRAFFIC CONTROL FOR WORK ON SHOULDERS	DRAWING NO. SHEET ___ OF ___
TOWN OF PARADISE	